



INTRODUCTION

HTT11 devices are modular devices that designed to measure and transmit the relative humidity, temperature and dew point. Model HTT08 devices transfer the temperature and humidity or dew point data to other controller devices by analog signals. Complying international standards, reliability and user friendly usage features are the design principles of these devices. So that, they are ergonomic

SAFETY PRECAUTIONS

- Before using the device, please read the warnings below and this guide carefully. The accidents or damages resulting from not following the warnings included in this guide are under user's responsibility.
- This device is intended to be used by qualified personnel in industrial environments, do not use in houselike environments.
- Do not use the device at places where corrosive, flammable and explosive gases exist. Contact points may create electrical discharge and this may cause explosion or fire.
- Do not allow metal fragments or lead wire scraps or liquid matters to fall inside this device. Otherwise fire or electrical shock may happen.
- Take the necessary precautions in order to prevent accidents and damages that may result in case the device gets faulty.
- There is no fuse or switch that brings the device in power down state, these should be added to the system by the user.
- Sensor and signalling cables should not be routed close to the power cables or inductive load cables.
- Do not power up the device before the connections related with the device are performed in accordance with connection diagram.
- Do not power up the device before the connections related with the device are performed in accordance with the connection diagram. While the device is powered, do not touch on the terminals.
- Configuration settings at factory out should be changed according to the user's preferences. The accidents and damages resulting from incorrect configuration settings are under users' responsibility.
- Never disassemble, repair and modify the device. These should be carried out by authorized service.
- Device lifetime is 10 years that is recommended by ministry.

Producer and Technical Service : ORDEL Ltd. Şti. Ostim OSB Mah. 1250. Cad. No: 10
06370 YENİMAHALLE / ANKARA
Tel:+90 312 385 70 96 (PBX) Fax: +90 312 385 70 78

PRODUCT CODE

HTT11 - 0 / / / / /

Supply Voltage

- 0= = 100-240Vac (Universal)
1= 24Vac/dc

Analog Outputs

- 0= N/A
1= 0/4-20mA Current Output
2= 0/2-10Vdc Voltage Output

Assembly Type

- 0= Wall Type
1= Canal Type
2= With Cable

Sensor Probe Length

- 1= 10 cm
2= 20 cm
3= 30 cm

Filter Type

- 2= Plastic

Temperature Range

- 0= 0 ... +60 °C
1= -40 ... +60 °C
2= -40 ... +120 °C

Sensor Probe Connection

- 0= N/A
1= Flange
2= ½" Fixed Raccord
3= ½" Adjustable Raccord

CONNECTION DIAGRAM

07	08	09	10	11	12
Out 1	Out -	Out 2	NC	L +	N -
Analog Outputs			Supply Voltage		

Out 1 = Temperature

Out 2 = Relative Humidity

TECHNICAL SPECIFICATIONS

Supply Voltage	100-240Vac/dc : +%10 -%15	24Vac/dc : +%10 -%20
Power Consumption	2W,3VA	
Analog Outputs	0/4-20mA (RL £ 500Ω)	0/2-10V (RL ³ 1MΩ)
Measurement Range	Humidity: 0 ... 100 %RH	Temperature: -40 ... +120 °C
Resolution	Humidity: 0,1%RH	Temperature: 0,1°C
Accuracy	Humidity: +/- 2 %RH (10%RH...90%RH) +/- 4 %RH (0%RH...100%RH)	Temperature: +/- 1°C (-20°C ... +70°C) +/- 2°C (-40°C ... +120°C)
Repeatability	Humidity: +/- 0,1%RH	Temperature: +/- 0,1°C
Sampling Period	100ms	
Operation Temperature	Device : -10°C ... +60°C	Sensorr : -40°C...+120°C
Storage Temperature	-20°C ... +70°C	
Protection	IP65	
Dimensions	Width : 115mm	Height : 95mm Depth : 56mm
Weight	210gr	

Document Num: KK-HTT0801-01